



General Information

Materijal broj	98685
Tip	zidna/stropna rasvjeta
Produkt segment	Unutarnja rasvjeta
Tema	ostalo/ nije dodijeljeno
Klasa energetske efikasnosti	F

Dimensions

Visina proizvoda (u mm/in)	145
Promjer proizvoda (u mm/in)	765
Neto težina (u kg)	3.4

Material & Colour

Materijal kućišta	plastika, čelik
Boja kućišta	crno, zlatno
Materijal stakla/sjenila	plastika sa granilom
Boja stakla/sjenila	prozirno

Functionality

Tip prekidača	bez prekidača
Funkcija	uključen daljinski upravljač nije moguća zamjena LED upravljanje preko daljinskog upravljača CCT
Baterija	Ne
Tip baterije	AAA; R03P; 1,5V

Technical Information

Stupanj zaštite	IP20
Klasa zaštite	2
Mrežni napon	220-240V,50/60Hz
Dimabilno	Yes
max. Snaga (1)	4X4,5W
max. Snaga (2)	3X4,5W
max. Snaga (3)	4X2,2W

Illuminant 1

Tip utičnice (1)	LED
Tip žarulje (1)	LED
Žarulja uklj. (1)	Uključeno
Lumen	2120;1590;1040
Kelvin	2700-6500K
Boja svjetla	TUNEABLE WHITE;TUNEABLE WHITE
Nominalni životni vijek (u h)	25000
Prebacivanje ciklusa	15000
Klasa energetske efikasnosti	F
Dimabilno	Yes
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Nazivna snaga lampe (preciznost 0,1W)	37
Tolerancija boje (LED, SDCM)	<6

Illuminant 2

Grlo (2)	LED
Tip žarulje (2)	LED
Žarulja uklj. (2)	Uključeno
Lumen	2120;1590;1040
Kelvin	2700-6500K
Boja svjetla	TUNEABLE WHITE;TUNEABLE WHITE
Nominalni životni vijek (u h)	25000
Prebacivanje ciklusa	15000
Dimabilno	Yes
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Nazivna snaga lampe (preciznost 0,1W)	37
Tolerancija boje (LED, SDCM)	<6

Illuminant 3

Grlo (3)	LED
Tip žarulje (3)	LED
Žarulja uklj. (3)	Uključeno
Lumen	2120;1590;1040
Kelvin	2700-6500K
Boja svjetla	TUNEABLE WHITE;TUNEABLE WHITE
Nominalni životni vijek (u h)	25000
Prebacivanje ciklusa	15000
Klasa energetske efikasnosti	F
Dimabilno	Yes
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Nazivna snaga lampe (preciznost 0,1W)	37
Tolerancija boje (LED, SDCM)	<6

						
4X4,5 W	2120l m	3X4,5 W	1590l m	4X2,2 W		

