
Project	
Notes	
Amount	
Date	


SALOBRENA 1 grid light
61351

PRODUCTSHEET

Technical Information

Material number	61351
Type	grid light
Max.Watt incl.transformer/driver	70
Illuminant Type (1)	LED
Lumen with Cover	5350
Kelvin Complete	4000K
Glass/Shade Material	plastic
UGR (Unified Glare Rating)	<19
Function	LED not replaceable
Directional Light	ZZDIRLI_N
Beamangle (in °)	120
Operation Voltage	220-240V,50/60Hz
Article Length (in mm/in)	1200
Article Width (in mm/in)	300
Article Height (in mm/in)	11
Installation Depth (in mm/in)	100
Protection Degree	IP20
Protection Class	2
Net Weight (in kg)	3.87
Colour Tolerance (LED, SDCM)	<6
Enclosure Material	aluminium
Enclosure Colour	white
colour code	RAL9003
lifetime (Lx)	L70
Nominal Lifetime (in h)	30000
Serial name	SALOBRENA 1







▯ 120
0X300

No liability is accepted for printing errors. All values are rated values. Power and luminous flux are subject to a tolerance of +/- 10%. Colour temperatures are subject to a tolerance of +/-150 Kelvin. Technical modifications reserved.